

CLICK ON THE NUMBERS OR TEXT TO JUMP TO THAT SECTION.



Staple Packs (Standard & Stainless Steel)	10-23
Staple Packs (Pro-Pack)	24-35
Plastic Hanger Insert Cards	36-47
Boxes	48-49
Clamshells	50-74
Glue Stick Bags	75-88
Wrap-around Labels	89-98
Labels	.99-110
Sleeves	111-123
Master/Inner Cartons	124-133
Tool Labels	134-135

LOGO - ACCEPTABLE USAGE



PASSWORD: Q2YbKrua

MASTER LOGO

The Arrow logo used on the front panel should ideally be in full-color and include the tagline:

HOW IT ALL COMES TOGETHER

except when size requirements would make it illegible, or when, for aesthetic purposes, it looks better removed.



ALTERNATE VERSIONS

The Arrow logo has alternate color variations to accommodate a variety of applications (e.g. back panel and side panels).

It is important to note the split chevron used in the one-color versions. These are not to be made into full-color logos and must always remain one color.







ONE-COLOR KNOCKED OUT



ONE-COLOR BLACK

LOGO - IMPROPER USAGE

*The only acceptable logos are listed on the previous page.

Do not modify the Arrow logo in any way.



DO NOT

CHANGE COLOR CONFIGURATION



DO NOT

CROP THE LOGO



DO NOT

MODIFY PLACEMENT OF THE CHEVRON



DO NOT

PLACE LOGO ON AN ANGLE



DO NOT

USE UNAPPROVED COLORS



DO NOT

CREATE BORDERS OR FRAMES



DO NOT

USE WITHOUT ICON



DO NOT

PLACE ON VISUALLY BUSY IMAGE



DO NOT

STRETCH OR DISTORT LOGO



DO NOT

FILL LOGO WITH AN IMAGE



DO NOT

USE WITHOUT ™



DO NOT

ADD DROP SHADOWS OR OTHER 3D EFFECTS

BRAND COLOR PALETTE

ARROW BRAND COLORS

The Arrow color palette consists of four colors — Arrow Bright Red, Arrow Dark Red, Arrow Black, and Arrow Gray.

Whenever possible, use Pantone colors for brand consistency. Color breakdowns are also provided for CMYK and RGB applications.


PRIMARY COLOR



ARROW BRIGHT RED

COATED PANTONE 186C
UNCOATED PANTONE 186U
CMYK 2/100/85/6
RGB 200/33/39
LAB 45/68/40
HEXIDECIMAL #C82127

SECONDARY COLORS



ARROW DARK RED

COATED PANTONE 188C
UNCOATED PANTONE 188U
CMYK 16/100/65/58
RGB 118/37/31
LAB 28/38/14
HEXIDECIMAL #76251F

ARROW GRAY

COATED PANTONE GRAY 7C
UNCOATED PANTONE GRAY 7U
CMYK 20/14/12/40
RGB 151/153/155
LAB 63/-1/-1
HEXIDECIMAL #97999B
ONE COLOR GRAY 0/0/0/40



ARROW BLACK

COATED PANTONE BLACK 6C
UNCOATED PANTONE BLACK 6U
CMYK 40/40/40/100
RGB 0/0/0
HEXIDECIMAL #000000
ONE COLOR BLACK 0/0/0/100

CONSUMABLE BADGE COLORS

RIVETS

When applicable, Arrow products are often identified by referencing their corresponding consumable (i.e. products that would utilize a T50 Staple). That reference is highlighted via the Consumable Badge, typically found in the upper right hand corner of the packages' front panel. Consumable Badges are color-coded for quick identification using the color values shown below.

STAPLES

LAB 69/-13/-35

HEX #65B2E8

JIAILL						KIVEIS	
Т50	PANTONE PROCESSED CYAN CMYK 100/0/0/0 RGB 0/174/239 LAB 62/-44/-50 HEX #00AEEF	HT65	PANTONE REFLEX BLUE C CMYK 100/93/14/12 RGB 0/22/137 LAB 15/32/-67 HEX #001689	WIDE CROWN #405	PANTONE 262C CMYK 67/91/40/35 RGB 83/40/79 LAB 24/25/-15 HEX #53284F	RIVET GREEN	PANTONE 354C CMYK 95/0/100/0 RGB 0/174/66 LAB 60/-77/40 HEX #00AE42
JT21	PANTONE 355C CMYK 99/12/100/2 RGB 0/149/59 LAB 52/-67/34 HEX #00953B	T18	PANTONE 227C CMYK 0/100/0/23 RGB 190/0/113 LAB 41/69/-8 HEX #BE0071	POWER CROWN #584	PANTONE 153C CMYK 20/65/100/7 RGB 192/107/19 LAB 55/31/58 HEX #C06B13	RIVET YELLOW	PANTONE 123C CMYK 0/23/91/0 RGB 255/198/41 LAB 84/13/78 HEX #FFC629
Т59	PANTONE 109C CMYK 1/16/100/0 RGB 255/209/0 LAB 62/-44/-50 HEX #FFD100	HT19	PANTONE 7709C CMYK 61/13/25/0 RGB 97/176/188 LAB 67/-23/-14 HEX #61B0BC	WIDE CROWN #854	PANTONE 7463C CMYK 100/80/43/45 RGB 0/43/73 LAB 16/-6/-24 HEX #002B49	RIVET BLUE	PANTONE PROCESSED CYAN CMYK 100/0/0/0 RGB 0/174/239 LAB 62/-44/-50 HEX #00AEEF
T25	PANTONE 471C CMYK 21/70/100/8 RGB 187/97/8 LAB 52/34/49 HEX #BB6125	Т30	PANTONE 2645C CMYK 32/42/0/0 RGB 174/149/218 LAB 66/20/-32 HEX #AE95DA	T75	PANTONE 021C CMYK 0/82/100/0 RGB 255/81/0 LAB 61/66/85 HEX #FF5100		
Т20	PANTONE 3275C CMYK 100/0/54/0 RGB 0/175/154 LAB 61/-71/-6 HEX #00AF9A	P35	PANTONE 149C CMYK 0/27/57/0 RGB 255/194/122 LAB 84/18/45 HEX #FFC27A	Т72	PANTONE 185C CMYK 2/100/92/0 RGB 234/0/41 LAB 50/77/49 HEX #EA0029		
P22	PANTONE 292C CMYK 56/16/0/0 RGB 101/178/232	T3 <i>7</i>	PANTONE 5493C CMYK 54/23/29/0 RGB 124/167/173				

LAB 66/-14/-8 HEX #7CA7AD

TO DOWNLOAD THE ARROW BRAND FONTS

PASSWORD: fB2rQU7F

HEADLINES & SUBHEADS

The typeface Futura LT Pro is to be used for headlines and subheads. The recommended font weight is Bold and the type should be in ALL CAPS. A headline should always be at least twice the point size of the subhead.

THIS IS A HEADLINE

THIS IS A SUBHEAD

FUTURA LT PRO BOLD

TRACKING: 20

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

abcdefghijklmn opqrstuvwxyz

1 2 3 4 5 6 7 8 9 0 `~!@#\$%^&*()_ +[]{}\|;:'".,<>/?

BODY COPY

The typeface Serifa STD should be used only for body copy. For most applications the recommended weight is Roman. When using light-colored type on a dark background, however, the weight of Bold can be used to prevent filling. The body copy should never be larger in point size than the subhead.

SERIFA STD Roman / Bold

TRACKING: 20

ABCDEFGHIJKLMN OPQRSTUVWXYZ ABCDEFGHIJKLMN OPQRSTUVWXYZ

abcdefghijklmn
opqrstuvwxyz
abcdefghijklmn
opqrstuvwxyz

1 2 3 4 5 6 7 8 9 0

`~!@#\$%^&*()_
+[]{}\|;:'".,<>/?

1 2 3 4 5 6 7 8 9 0

`~!@#\$%^&*()_
+[]{}\|;:'".,<>/?

ICON LIBRARY











SANDING







































For ease of use and to help maintain consistency across all packaging, many of the product feature and safety icons, consumable, and other badges have been pre-designed for you. Click on the link above to view and download those assets.

TRANSLATIONS

PACKAGING REGULATIONS REGARDING TRANSLATIONS

In an effort to maintain compliance globally, Arrow packaging must adhere to certain standards and regulations regarding the translations of text on its packaging. Those regulations are as follows:

- All mandatory label information must be shown in English, French, and Spanish, except the dealer's name and address which can appear in either language.
- Any label information in addition to the mandatory requirements discussed above (i.e. promotional statements, etc.) does not have to appear in a bilingual manner. Dealers are, however, encouraged to include such information in English, French, and Spanish.
- For readability, all translations must be shown at a **MINIMUM SIZE OF 4PT.**
- English, French, and Spanish must be of equal prominence. All product packaging for weight, size, etc. must be labeled in metric.
- All product icons, consumable badges, and product descriptions, must contain translations. Refer to the screenshots in each section to confirm whether or not a particular element requires a translation, and for guidance on layout.





STAPLE PACK LAYOUT OVERVIEW

CLICK ON THE NUMBERS OR TEXT BELOW TO JUMP TO THAT SECTION.



BACK PANEL Stainless Steel #504SS1™ 1/4" 6mm STAINLESS STEEL Acero in oxidable Acier in oxydable 8 BEST FOR: OPTIMAL POUR: IDEAL PARA: • Paper • Papel • Papier • Light Fabric • Tela ligera • Tissu léger • Thin Plastic • Plástico delgado • Plastique mince STAPLES COMPATIBLE WITH: • GRAPAS COMPATIBLES CON: • AGRAFES COMPATIBLES AVEC: ARROW • POWERSHOT • STANLEY • BOSTITCH • DEWALT • SUREBONDER ITEM# 504SS1 © 2022 Arrow Fastener Company, LLC Arrow, T50 and 504SS1 are trademarks of Fastener Company, LLC 271 Mayhill Street Saddle Brook, New Jersey 07663 USA Designed and Assembled in USA Diseñado y ensamblado en EE.UU. Conçu et assemblé aux É.-U.





SIDE PANELS



- 1. GRAPHIC ELEMENTS
- 2. CONSUMABLE BADGE
- 3. COLOR BRAND BAR
- 4. ARROW LOGO
- 5. PRODUCT DESCRIPTIONS
- 6. PRODUCT PHOTOGRAPHY
- 7. PRODUCT FEATURE ICONS
- 8. ADDITIONAL PRODUCT INFO
- 9. UPC, SAFETY ICONS & TEXT

COMPLETED STAINLESS STEEL STAPLE PACK TEMPLATE

SIDE PANEL


BACK PANEL

SIDE PANEL



COMPLETED STANDARD STAPLE PACK TEMPLATE


SHELL



CREATING YOUR SPACING GUIDE

STEP 1 (IMPORTANT)

In this step you will be creating a guide that will determine the spacing for all package design elements. Start by scaling the <u>logo</u> to **1/2 the width of the front panel** of the package.



STEP 2

Using the logo at this size, **cut the chevron in** half to create your spacing and layout guide. Additionally, in this package type, you will also make use of a **quarter chevron** for smaller spaces. Note color differences below.



STEP 3

Use half and quarter chevron sizing tool to determine proper spacing of subsequent graphic/text elements as shown below.




GRAPHIC ELEMENTS (1)



PASSWORD: 7Fwcwh4T

METALLIC TEXTURE

To be used as a background image, the metallic texture should fill approximately 1/2 the height of the front facing panel.




FRONT PANEL



Dotted line denotes the centerpoint of the panel.

CORNER TRIANGLE

The corner triangle is a graphic element that should span 1/2 the height of the front panel. The dark red portion of the triangle should be determined using **3 half chevrons**.



CONSUMABLE BADGE (2)




STEP 1

For staple packaging, the consumable badge is a pre-built element that can be downloaded from the icon library. Check with your project manager for which consumable badge(s) to use.

STEP 2

To determine the correct size of each badge, place 4 consumable badges horizontally across the top of the **front panel**, then scale to fit the width. Place one of those badges in the upper right flush to the die line. The background color of the consumable badge will extend from the bottom of the front panel all the way up to the fold line indicated in the diagram.




STEP 1

The height of the brand bar should be equal to 1 of your half chevron spacers.



STEP 2

To determine the width of the dark red color, use 7 half chevron spacers flipped 90° to measure the distance from the front panel consumable color badge to the tip of the dark red.



STEP 1

FRONT PANEL: To determine the size and placement of the logo, place **one half chevron spacer** flush against the far left die line, one against the bottom of the color brand bar, and one flush against the left edge of the consumable badge. Then scale the logo to fit within the spacers.

FRONT PANEL



STEP 2

FRONT PANEL: Once the logo is properly scaled and placed within the top, left, and right spacers, add an additional **half chevron** at the bottom to maintain uniform spacing on all sides.



TOP AND BOTTOM PANELS: To find proper logo sizing and placement on these panels, place a half chevron spacer along the left edge, and utilize the quarter chevron spacer for the top and bottom edges.

PRODUCT DESCRIPTIONS




TOP, BOTTOM, AND SIDE PANELS

NOTE: For these areas where vertical space is limited, you will be using BOTH the quarter chevron spacer and the half to find your live area. See below.

STEP 1: Begin with **top panel**. Place 1 quarter chevron spacer at the top and bottom edges and then utilize your standard 1 half chevron spacer on the right die line. (Extend live area all the way to the right edge of the logo).



STEP 2: Using the font <u>Futura LT Pro Bold</u> for all product descriptions, stack the **model number** and the **staple size**. Group the text, and **right-align** it within the live area.



STEP 3: To the left of your newly formed text block, add the **staple gun type** and translations using the same font as the previous step. Group the text and **center-align** it between the logo and the text block from step 2. Group, then copy and past all elements (including logo) into the **bottom panel** using the same spacers.



STEP 4: For the **inner box side panels**, copy and paste all elements from the previous steps (including the logo) and adjust spacing between elements to fit within the area, maintaining proper spacing from the edges using your spacers.



FRONT PANEL

BLUE PANEL WITH PEG HOLE: The content of this panel differs slightly as we are now excluding the model number and the logo from the lockup. To find your live area, place your **half chevron spacer** against **all** edges of the front panel, starting below the peg hole as shown. Using the font <u>Futura LT Pro Bold</u>, place your **staple gun type**, followed by the **application type**, followed by the **staple size**. Group the text, scale to fit within your spacers and center align the group.

BOTTOM BRAND TRIANGLE: To find your live area, place your **half chevron spacer** against the left and bottom edges. Use a **quarter chevron spacer** for the area above the text. Use <u>Serifa STD Bold</u> for this text.



NOTE: The minimum size for <u>translation text</u> is 4pt, and the translations must always be the same size as its English counterpart.

PRODUCT PHOTOGRAPHY 6

FRONT PANEL

The "live area" for the front panel photography can be found using your spacers. Inside of the corner triangle area, start by placing 1 quarter chevron spacer above your previously placed product product description text. Add 1 half chevron to against the left edge. Using your best judgment, fill the live area accordingly, keeping photography within the corner triangle.

FRONT PANEL



PRODUCT FEATURE ICONS



PRODUCT ICON

FEATURE/BENEFIT ICONS


SIZE: Width of the USA badge and stainless steel badge (when applicable) should be scaled down to 3/4 the width of the front panel consumable badge. Additional icons should be no less than 1/2 the width of the USA badge.


TRANSLATIONS: <u>Translations</u> for the USA badge and stainless steel badge should be placed directly underneath each badge. **Use best judgment.** The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

PLACEMENT: Create a live area for the relevant product icons by placing 1 half chevron spacer from the left edge of the consumable badge, and keep at least 1 half chevron spacer away from any other elements or edges. **Use best judgment.**

FRONT PANEL







NOTE:

Unlike the "stainless steel" staple pack template, the "standard" staple pack template does **not** include a stainless steel icon, resulting in a slightly altered layout on the product feature icon page. See completed standard staple pack template for alternate layout.

ADDITIONAL PRODUCT CALLOUTS/BADGES



APPLICATION EXAMPLE BADGES

NOTES: Refer to project manager for up to date assets for this area. Create a live area for the assets by adding a half chevron spacer on all edges of the panel, and a half chevron (or quarter chevron when space is extremely limited) above the UPC/safety icon/text area on the next page.

The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

Use best judgment in recreating the examples provided in terms of placement and sizing of the elements specified below.

SHELL BACK PANEL - T50 AND JT21 STAPLE PACKS




SHELL BACK PANEL - OTHER STAPLE TYPES (BACK VARIES)



NOTES: Using your **half chevron** and **quarter chevron** spacers as pictured below, find your live area for the UPC/Safety Icons/Text. Place elements according to the hierarchy shown below. The item # and website use the font <u>Futura LT Pro Bold</u>. All other text in this area is use font <u>Serifa STD Bold</u>. **Use best judgment** to keep font size readable for the consumer, and for the placement of the UPC, safety icons and text. Always maintain spacing from elements and egdes using your half chevron spacer (or quarter chevron spacer when space is extremely limited.)

The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

*Always confirm the most up to date numbers and information from Product Manager prior to releasing files.



NOTE: This flap is located on the backside of the **slide tray** and will not be visible when the box is fully assembled.

PRO-PACK LAYOUT OVERVIEW

CLICK ON THE NUMBERS OR TEXT BELOW TO JUMP TO THAT SECTION.

TOP PANEL








BOTTOM PANEL, SIDE PANEL A, + SIDE PANEL B



- 1. GRAPHIC ELEMENTS
- 2. CONSUMABLE BADGE
- 3. COLOR BRAND BAR
- 4. ARROW LOGO
- 5. PRODUCT DESCRIPTIONS
- 6. PRODUCT PHOTOGRAPHY
- 7. PRODUCT FEATURE ICONS
- 8. ADDITIONAL PRODUCT INFO
- 9. UPC, SAFETY ICONS & TEXT

COMPLETED PRO-PACK TEMPLATE



CREATING YOUR SPACING GUIDE

STEP 1 (IMPORTANT)

In this step you will be creating a guide that will determine the spacing for all package design elements. Start by scaling the <u>logo</u> to **1/2 the width of the front panel** of the package.



FRONT PANEL

STEP 2

Using the logo at this size, **cut the chevron in** half to create your spacing and layout guide. Additionally, in this package type, you will also make use of a **quarter chevron** for smaller spaces. Note color differences below.



STEP 3

Use half and quarter chevron sizing tool to determine proper spacing of subsequent graphic/text elements as shown below.



GRAPHIC ELEMENTS (1)

1/4"

T50[®]

STAPLES GRAPAS

TO DOWNLOAD THE

PASSWORD: 7Fwcwh4T

FRONT PANEL

METALLIC TEXTURE

To be used as a background image, the metallic texture should fill approximately 1/2 the height of the front facing panel.



AGRAFES 1/4" PRO-PACK 6mm Pro-Pack Paquete profesional Emballage Pro #504IP™ DESIGNED AND ASSEMBLED IN USA Designed and assembled in USA Diseñado y ensamblado en USA Conçues et emballées aux États-Unis 5000 QTY. | CANT. | QTÉ.

HOW IT ALL COMES TOGETHER


Ajuste Universal

Ajustement Universel

Dotted line denotes the centerpoint of the panel.

CORNER TRIANGLE

The corner triangle is a graphic element that should span 1/2 the height of the front panel. The dark red portion of the triangle should be determined using 3 half chevrons.



CONSUMABLE BADGE

TO ACCESS THE FULL **PRODUCTICON** LIBRARY

STEP 1

For staple packaging, the consumable badge is a pre-built element that can be downloaded from the icon library. Check with your project manager for which consumable badge(s) to use.

STEP 2

To determine the correct size of each badge, place 4 consumable badges horizontally across the top of the front panel, then scale to fit the width. Place one of those badges in the upper right flush to the die line. The background color of the consumable badge should also extend to the full height of the front panel for staple packs.



width = 1/4 total front

COLOR BRAND BAR (3)


FRONT PANEL

STEP 1: The height of the brand bar should be equal to **1 of your half chevron spacers**.

FRONT PANEL



STEP 2: To determine the width of the dark red color, use **7 half chevron spacers** flipped 90° to measure the distance from the front panel consumable color badge to the tip of the dark red.




TOP PANEL

STEP 1: The height of the brand bar should be equal to **3 of your half chevron spacers**.



STEP 2: On this panel, the dark red and bright red will be reversed. To determine the width of the bright red color, use **11 half chevron spacers** flipped 90° to measure the distance from the right edge of the panel to the tip of the dark red.



STEP 1

FRONT PANEL: To determine the size and placement of the logo, place **one half chevron spacer** flush against the far left die line, one against the bottom of the color brand bar, and one flush against the left edge of the consumable badge. Then scale the logo to fit within the spacers.

STEP 2

FRONT PANEL: Once the logo is properly scaled and placed within the top, left, and right spacers, add an additional **half chevron** at the bottom to maintain uniform spacing on all sides.

TSO® STAPLES PROPERTY TO THE STAPLES AGRAFES #504IP TO THE STAPLES AGRAFES

STEP 3

TOP PANEL: The size of the logo for the top panel should be 50% of the width of the main logo from the front panel. Place the logo one half chevron spacer away from the left edge, then center it vertically between the top of the panel, and the top of the color brand bar.

BOTTOM PANEL, SIDE PANEL A, AND SIDE PANEL B: Do **not** insert the logo for these panels at this time. See bottom of the following page for instructions on how to place Arrow logo and other content on these panels.

PRODUCT DESCRIPTIONS













TOP PANEL

STEP 1: Begin with the top panel. Place 1 half chevron spacer flush against the right edge and then utilize the height of the logo on the top panel to create a live area for the following steps.

STEP 2: Using the font <u>Futura LT Pro Bold</u> for all product descriptions, stack the **model number** and the **staple size**. Group the text, and **right-align** it within the live area.

STEP 3: To the left of your newly formed text block, add the **staple gun type** (and <u>translations</u>) using the same font as the previous step. Group the text and **center-align** it between the logo and the text block from step 2. (Always maintain a minimum spacing of 1 half chevron between each element.)

STEP 4: Next, add the **quantity** and the **pro pack description** over the color brand bar area on the top panel as shown. Create a live area using half chevron spacers on the sides and quarter chevron spacers on the top and bottom. **Use best judgment.**

BOTTOM PANEL, SIDE PANEL A, AND SIDE PANEL B

STEP 5: Group all of the elements from the previous steps together (logo, staple gun type, model number, and staple size.) Create a live area on the bottom panel, side panel A, and side panel B by adding 1 half chevron spacer to each of the edges. Paste the entire group of elements and scale to fit within the spacers.

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

PRODUCT PHOTOGRAPHY 6

FRONT PANEL

The "live area" for the front panel photography can be found using your spacers. Inside of the corner triangle area, start by placing 1 quarter chevron spacer above your previously placed product product description text. Add 1 half chevron to against the left edge. Using your best judgment, fill the live area accordingly, keeping photography within the corner triangle.



PRODUCT FEATURE ICONS



PRODUCT ICON LIBRARY

FEATURE/BENEFIT ICONS

SIZE: The pro-pack icon should be the same width as the consumable badge. The width of the USA badge should be scaled down to 3/4 the width of the front panel consumable badge. Additional icons should be no less than 1/2 the width of the USA badge.

TRANSLATIONS: <u>Translations</u> for the pro-pack icon and USA badge should be placed directly underneath each badge. The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart. **Use best judgment.**

PLACEMENT: Create a live area for the relevant product icons by placing 1 half chevron spacer from the left edge of the consumable badge, and keep at least 1 half chevron spacer away from any other elements or edges. **Use best judgment.**

FRONT PANEL





		GNED	ANI	
	L	J\$	A	
1	1	1	1	- 1
1	1/4 6mn		1	! !
1	- 1	- 1	- 1	- 1

ADDITIONAL PRODUCT CALLOUTS/BADGES

APPLICATION EXAMPLE BADGES

NOTES: Refer to project manager for up to date assets for this area. Create a live area for the assets by adding a half chevron spacer on all edges of the panel, and a half chevron (or quarter chevron when space is extremely limited) above the UPC/safety icon/text area on the next page.

The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

Use best judgment in recreating the examples provided in terms of placement and sizing of the elements specified below.



UPC/SAFETY ICONS/TEXT (9)

NOTE: Using your **half chevron** and **quarter chevron** spacers as pictured below, find your live area for the UPC/Safety Icons/Text. Place elements according to the hierarchy shown below. The item # and website use the font <u>Futura LT Pro Bold</u>. All other text in this area is use font <u>Serifa STD Bold</u>. **Use best judgment** in font size, and placement of the UPC, safety icons and text. Always maintain spacing from elements and egdes using your half chevron spacer (or quarter chevron spacer when space is extremely limited.)

The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

Safety icons can be downloaded from the icon library.

*Always confirm the most up to date numbers and information from Product Manager prior to releasing files.

ITEM# 504IP SAFETY ICONS UPC WEBSITE 2021 Arrow Fastener Company, LLC Arrow, T50 and 504 are trademarks of Arrow **COPYRIGHT INFO** Fastener Company, LLC **CORPORATE** 271 Mayhill Street Saddle Brook, New Jersey 07663 USA **ADDRESS** Designed and Assembled in USA Diseñado y ensamblado en EE.UU MANUFACTURING Concu et assemblé aux É.-U. LOCATION (and translations) **REVISION DATE PACKAGING** MATERIAL


NUMBER

BACK PANEL



PLASTIC HANGER INSERT CARD LAYOUT OVERVIEW

CLICK ON THE NUMBERS OR TEXT BELOW TO JUMP TO THAT SECTION.



BACK PANEL



- 1. GRAPHIC ELEMENTS
- 2. CONSUMABLE BADGE
- 3. COLOR BRAND BAR
- 4. ARROW LOGO
- 5. PRODUCT DESCRIPTION
- 6. PRODUCT FEATURE ICONS
- 7. ADDITIONAL PRODUCT CALLOUTS
- 8. UPC, SAFETY ICONS & TEXT

COMPLETED PLASTIC HANGER INSERT CARD TEMPLATE

NOTE: Shape and layout of the plastic hanger insert cards may vary dramatically depending on the size and shape of the product. Follow the example found in this guide wherever possible and use best judgment based on the space available.


NOTE: All graphic elements should be properly spaced from the blue die line. Yellow or green grayed out areas denote plastic clips or notches and should not contain text, icons, or logos. Try to keep space from these areas if possible.



CREATING YOUR SPACING GUIDE

STEP 1 (IMPORTANT)

In this step you will be creating a guide that will determine the spacing for all package design elements. Start by scaling the <u>logo</u> to 1/2 the width of the front panel of the package.



STEP 2


Using the logo at this size, **cut the chevron in half** to create your spacing guide. For smaller areas like those found on the back panel, a quarter chevron spacer will also be used.



STEP 3

half chevron

Use half and quarter chevron sizing tool to determine proper spacing of subsequent graphic/text elements as shown below.



GRAPHIC ELEMENTS



GRAPHIC ELEMENTS

PASSWORD: 7Fwcwh4T


METALLIC TEXTURE

Metallic texture should be used as a background image to aid in the transition from white to the red graphics below. Beginning in the upper half, it should gradually begin to fade to white above the center point as shown on the right.




CORNER TRIANGLE

The corner triangle is a graphic element that should span 1/2 the height of the front panel in its entirety. The dark red portion of the triangle should be determined using 3 half chevrons.



MADE IN USA GRAPHIC

When applicable, the American flag graphic should take up approximately 1/8 of the panel height and bleed off the edge. The "Made in USA" text should be placed on top of the flag (use best judgment and do not extend any part of the text off of the edge.)




CONSUMABLE BADGE (2)

STEP 1

For plastic hanger insert cards, the consumable badge is a prebuilt element that can be downloaded from the icon library. **Check** with your project manager for which consumable badge(s) to use.

STEP 2

To determine the correct size of each badge, divide the **front panel** into thirds, then place the consumable badge to fill the width of the far right third. The background color of the consumable badge will span the entire height of the front panel as shown.



CONSUMABLE BADGE width = 1/3 total front panel area


STEP 1

The height of the brand bar should be equal to 1 of your half chevron spacers.



STEP 2

To determine the width of the dark red color, use **7 spacers** flipped 90° to measure the distance from the front panel consumable color badge to the tip of the dark red.



STEP 1


To determine the size and placement of the logo, place one spacer flush against the far left die line, one against the center hole punch die line, and one flush against the consumable badge. Then scale the logo to fit within the spacers.


NOTE: Always maintain proper logo ratios as per brand guidelines. Do not stretch or distort the logo to fit.



STEP 2

Once the logo is properly scaled and placed within the top, left, and right spacers, add an additional half chevron at the bottom to maintain uniform spacing on all sides.







PRODUCT DESCRIPTION

To find your exact live area for your product description (and translations), add 1 spacer underneath the logo, one along the consumable badge, and then one from each of the neighboring die lines as shown in the diagram.


FONT: Futura LT Pro Bold

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

PRODUCT FEATURE ICONS



PRODUCT ICON LIBRARY




FEATURE/BENEFIT ICONS

SIZE/PLACEMENT: Determine your live area by placing one **half** chevron below the "product descriptions" section, then one **quarter** chevron on each of the neighboring edges or no-print areas. As available space will vary, **use best judgment** for determining the bottom of yout live area.

Beginning at the top of the live area, stack icons (with <u>translations</u> below) and size to the live area **using best judgment**.

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

ADDITIONAL PRODUCT CALLOUTS



ADDITIONAL CALLOUTS

In the bright red area of your corner triangle, create a live are for additional callouts by adding half or quarter chevrons as shown below, taking into account that you may need to place your spacer against a no-print area rather than the die line. **Use best judgment** when aligning the content (and translations) within the live area so that the overall design appears balanced.

FONT: Futura LT Pro Bold

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.


UPC/SAFETY ICONS/TEXT (8)

NOTES: This is one circumstance where use of spacers may not be possible due to extremely limited area. Use best judgment to maintain readability when placing text, UPC, safety icons, steering clear of the die line. The item # and website use the font Futura LT Pro Bold. For all other text in this area, use font Serifa STD Bold.

The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

Safety icons can be downloaded from the icon library.

*Always confirm the most up to date numbers and information from Product Manager prior to releasing files.





BOX LAYOUT OVERVIEW

CLICK ON THE NUMBERS OR TEXT BELOW TO JUMP TO THAT SECTION.










INNER PANEL

- 1. GRAPHIC ELEMENTS
- 3. COLOR BRAND BAR
- 5. PRODUCT DESCRIPTIONS
- 7. PRODUCT FEATURE ICONS
- 9. UPC, SAFETY ICONS & TEXT
 10. EXTRA CONTENT AREA

- 2. CONSUMABLE BADGE
- 4. ARROW LOGO
- 6. PRODUCT PHOTOGRAPHY
- 8. ADDITIONAL PRODUCT INFO

COMPLETED BOX TEMPLATE



CREATING YOUR SPACING GUIDE

STEP 1 (IMPORTANT)

In this step you will be creating a guide that will determine the spacing for all package design elements. Start by scaling the <u>logo</u> to **1/2 the width of the front panel** of the package.



STEP 2

Using the logo at this size, **cut the chevron in half** to create your spacing and layout guide.



STEP 3

Use half chevron sizing tool to determine proper spacing of subsequent graphic/text elements as shown below.




GRAPHIC ELEMENTS (1)

GRAPHIC ELEMENTS

PASSWORD: 7Fwcwh4T

METALLIC TEXTURE

To be used as a background image, the metallic texture should fill approximately 1/2 the height of its respective panel.



centerpoint

FRONT PANEL

AND NAILER
GRAPADORA ELÉCTRICA
Y CLAVADORA
AGRAFEUSE ÉLECTRIQUE
ET CLOUSEUSE

13GA
IRAD NAILE
BRAD NAILE
GRAPADORA
GRAPEUSE ÉLECTRIQUE

HAND MA

CON

arrow 2

I I dark red

triangle width

dark red triangle width

BACK PANEL



The back panel triangle is the same size as front panel (½ the height of the panel) but solid dark red only.

CORNER TRIANGLE

The corner triangle is a graphic element that should span ½ the height of the front panel in its entirety. On the front panel, the width of the dark red portion of the triangle should be determined using 3 half chevrons.

On the side panels, the tip of the corner triangle will align with the bottom of the Arrow logo. The width of the dark red portion of the triangle is 1 half chevron.

extend triangle to bottom of logo extend triangle to bottom of logo extend triangle to bottom of logo ELECTRIC STAPLE GUN AND NAILER GRAPADORA ELÉCTRICA Y CLAVADORA AGRAFEUSE ÉLECTRIQUE ET CLOUSEUSE HOW IT ALL COMES TOGETHER ELECTRIC STAPLE GUN AND NAILER GRAPADORA AGRAFEUSE ÉLECTRIQUE ET CLOUSEUSE HANT DUTY BUTTAL STAPLES CLAVOS DE LA PARIS CLAVO

CONSUMABLE BADGE (2)




STEP 1

For box packaging, the consumable badge is a pre-built element that can be downloaded from the icon library. Check with your project manager for which consumable badge(s) to use.

STEP 2

To determine the correct size of each badge, place 5 consumable badges horizontally across the top of the front, then scale to fit the width. Place one of those badges in the upper right flush to the die line. If there is more than one consumable badge, stack them **vertically** on the front panel.

NOTE: The side panel badge will be 2/3 the size of the front panel badge and stacked **horizontally** in the event there is more than 1 badge.



FRONT PANEL BADGE width = 1/5 total front panel area

SIDE PANEL BADGE width = 2/3 badge on front panel


STEP 1

The height of the brand bar should be equal to 1 of your half chevron spacers.



STEP 2

To determine the width of the dark red color, use **7 spacers** flipped 90° to measure the distance from the front panel consumable color badge to the tip of the dark red.



STEP 3

Place one of the flipped spacers from the previous step on the far left side of your brand bar. This will show you where to place your product number (e.g. T50DCD). The height of the product number text should not exceed 50% of the brand bar height and should be centered between top and bottom of the brand bar.


Use the font Futura LT Pro Bold in all caps for the product number both here and on the side panel.



NOTE: "T50ACN" (the item #) may also appear in other areas outside of the color brand bar. **See** "**Product description**" **section**.

FRONT PANEL

To determine the size and placement of the logo, place one spacer flush against the far left die line, one against the top brand bar, and one flush against the centerpoint. Then scale the logo to fit within the spacers. Padding around the logo should always be 1 spacer on all sides.



SIDE PANEL

After you complete the placement and sizing of the logo on the front panel, copy and paste the logo as is onto the side panels. The logo should then be placed 1 spacer from the left edge of the panel, and 1 spacer from the top edge on the panel.



INNER PANEL

The logo is the only element on the inner panel, knocked out in white against the Arrow bright red. Place 1 spacer from the top and bottom edges and place the logo (centered on the panel) between these 2 spacers.



NOTES:

Always maintain proper logo ratios as per brand guidelines. Do not stretch or distort the logo to fit. Padding around the logo should always be 1 spacer on all sides.

PRODUCT DESCRIPTIONS



MAIN PRODUCT DESCRIPTION

FRONT AND BACK PANELS: Place your main product description (and <u>translations</u>) directly to the right of the logo with a distance of no less than 1 spacer. Similar to the logo, be sure to maintain proper spacing of the live text area from both the top bar and the consumables badge (or the top and right edge of the back panel).

FEECTRIC STAPLE GUNTAND RUSING THINNER

AND NAILER

GRAPADORA ELÉCTRICA

Y CLAVADORA

AGRAFEUS ÉLECTRIQUE

FT CLOUSEUSE

186A

BRAD NAILS

CRAVOS DIN

CLOUS SANS TÎTE

CONCAC MANTANDE HINNER

CONCAC MANTANDE

CONCAC

FONT: Futura LT Bold

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

NOTE: For package types that contain **more** than 1 item, this space is reserved for the product quantity as shown below.



(The example doesn't have a product quantity in this area because it only contains 1 item.)

ELECTRIC STAPLE GUN AND NAILER GRAPADORA ELÉCTRICA Y CLAVADORA AGRAPADORA ELÉCTRICA Y CLAVADORA AGRAPEUSE ÉLECTRIQUE ET CLOUSEUSE

Maximum Power With Every Shot

Consistent Powerful Drive Force

Consistent Powerful Drive Force

Consistent Powerful Drive Force

Pulseance Maximal & Cheque Tir

Producion Maxima Con Cudit Tiro

Podencia Maxima Con Cudit Tiro

Tindinys Seguridad de Contacto

Too's STAPLES

July Seguridad de Contacto

SIDE PANELS: Place your main product description (and translations) directly to the right of the logo with a distance of no less than 1 spacer. The product description should be three lines (one for each translation) and should not exceed the height of the logo. You'll need to reserve some space to the right of the product description text for product photography on this panel as shown.



ITEM # PLACEMENT (SIDE PANELS)

The placement of the item # on the side panel differs from the front because there is no brand bar. The item # should be placed 1 spacer from the top, 1 spacer from the right edge of the panel.

FONT: Futura LT Bold



PRODUCT PHOTOGRAPHY 6

FRONT PANEL

Product photography should take up approximately 2/3 of the front panel, slightly overlapping the red triangle graphic. Photo should be at least one 1/2 chevron from all other cover text and icons.



BACK PANEL

Product photography should take up approximately 1/2 of the back panel. Photo on back will be smaller than the front panel to account for space to add product call-outs.



SIDE PANELS

The "live area" for the side panel photography can be found using your spacers. **Using your best judgment**, fill the live area accordingly.



front panel photo = 2/3 front panel width

PRODUCT FEATURE ICONS



PRODUCT ICON

FEATURE/BENEFIT ICONS


SPACING: Relevant product icons (and <u>translations</u>) should be placed on the right side of the front panel. Icons and their translations should be stacked vertically, spacing the icons evenly within the live area. Icons should be 1 half chevron away from all edges or elements (translations may need slightly more room, use best judgment).

SIZE: Width of the icons should be scaled down to 2/3 the width of the front panel consumable badge.

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

FRONT PANEL





ADDITIONAL PRODUCT CALLOUTS/BADGES



FEATURE & BENEFIT CALLOUTS

Utilize the open space surrounding the product photography to place any additional product callouts (and <u>translations</u>) using the Serifa Bold font. For heirarchy purposes, font size of callouts should be smaller than the font size used for the product description to the right of the logo.


FONT: Serifa STD Bold

EXTENDED CONSUMABLE BADGE

A more detailed version of the consumable badge from the front panel, this pre-built element will live on the back panel within the designated content area. Always use your spacers to maintain a minimum padding around any element. Check with your project manager whether or not your package will contain an extended consumable badge. This element can be downloaded from the icon library.

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

BACK PANEL



UPC/SAFETY ICONS/TEXT (9)

NOTES: Using your half chevron spacers as pictured below, find your live area for the UPC/Safety Icons/Text. Place elements according to the hierarchy shown below. The item # and website use the font <u>Futura LT Pro Bold</u>. For all other text in this area, use the font <u>Serifa STD Bold</u>. **Use best judgment** to keep font size readable for the consumer, and for the placement of the UPC, safety icons, and text. Always maintain spacing from elements and egdes using your half chevron spacer (or quarter chevron spacer when space is extremely limited.)

The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

Safety icons can be downloaded from the icon library.

*Always confirm the most up to date numbers and information from Product Manager prior to releasing files.

BACK PANEL



BACK PANEL



NOTES: Depending on the product type, this area should be used for any legal mandatories such as product warnings. **Use your best judgment** on spacing based on the required text for each product. Make sure to maintain proper padding around text area by utilizing your spacer.

The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.



CLAMSHELL INSERT CARD OVERVIEW

CLICK ON THE NUMBERS OR TEXT BELOW TO JUMP TO THAT SECTION.



- 1. GRAPHIC ELEMENTS
- 2. CONSUMABLE BADGE
- 3. COLOR BRAND BAR
- 4. ARROW LOGO

- 5. PRODUCT DESCRIPTIONS
- 6. PRODUCT FEATURE ICONS
- 7. ADDITIONAL PRODUCT INFO
- 8. UPC, SAFETY ICONS & TEXT

COMPLETED CLAMSHELL TEMPLATE

FRONT PANEL



NOTE: Once assembled, this flap will be folded over and displayed over the no print area on the back panel.





NOTE: The yellow glue gun outline is to show where the product will be placed. This is a no print area.

STEP 1 (IMPORTANT)

In this step you will be creating a guide that will determine the spacing for all package design elements. Start by scaling the <u>logo</u> to **1/2 the width of the front panel** of the package.



STEP 2

Using the logo at this size, **cut the chevron in half** to create your spacing and layout guide.



STEP 3

Use half chevron sizing tool to determine proper spacing of subsequent graphic/text elements as shown below.



GRAPHIC ELEMENTS (1)



PASSWORD: 7Fwcwh4T

METALLIC TEXTURE


To be used as a background image, the metallic texture should fill approximately 1/2 the height of its respective panel.



dotted line = panel height centerpoint

CORNER TRIANGLE


The corner triangle is a graphic element that should span 1/2 the height of the front panel in its entirety. The dark red portion of the triangle should be determined using 3 half chevrons.



For the back panel, maintain the size of the large triangle from the front, but fill the entire triangle using the dark red.

FRONT PANEL

BACK PANEL







CONSUMABLE BADGE (2)


PRODUCT ICON LIBRARY

STEP 1

For clamshell packaging, the consumable badge is a pre-built element that can be downloaded from the icon library. Check with your project manager for which consumable badge(s) to use.

STEP 2

To determine the correct size of the consumable badge, place 4 consumable badges side by side and horizontally scale to fit the width of the **front** of the package. Place the consumable badge in the bottom right corner of the front panel.



FRONT PANEL BADGE width = 1/4 total front panel area

STEP 1

The height of the brand bar should be equal to 2 of your half chevron spacers.



STEP 2

To determine the width of the dark red color, use **7 spacers** flipped 90° to measure the distance from the front panel consumable color badge to the tip of the dark red.



STEP 3

Using one of the flipped spacers from the previous step on the far left side of your brand bar will show you where to place your product number (e.g. GT11.) The height of the product number text should not exceed 50% of the brand bar height and should be centered between the top and bottom of the brand bar. Use the font Futura LT Pro Bold in all caps for the product number.




NOTE: "GT11" (the item #) may also appear in other areas outside of the color brand bar. **See** "Product description" section.

STEP 1

To determine the size and placement of the logo, place one spacer flush against the far left die line, one against the top brand bar, and one flush against the centerpoint. Then scale the logo to fit within the spacers.

NOTE: Always maintain proper logo ratios as per brand guidelines. Do not stretch or distort the logo to fit.




STEP 2

Once the logo is properly scaled and placed within the top, left, and right spacers, add an additional half chevron at the bottom to maintain uniform spacing on all sides.

BACK PANEL: Logo on the front and back of the insert card should be the same size, using the knocked out version of the logo.







BACK PANEL

PRODUCT DESCRIPTIONS

FRONT PANEL



MAIN PRODUCT DESCRIPTION

FRONT PANEL: Located to the right of the Arrow logo and at least 1 spacer away from the logo edge, place the product description text in all caps (e.g. Mini Glue Gun plus <u>translations</u> stacked vertically below.) Size the product description text based on the designated area for the package type.

BACK PANEL: The back panel product decription and item # placement remains the same except everything sits on a solid red background and is knocked out in white.



BACK PANEL

ITEM # PLACEMENT (BACK PANEL)

The placement of the item # on the back panel differs from the front because there is no brand bar. The item # should be placed 1 quarter chevron spacer from the top, and 1 half chevron spacer from the right edge of the panel.

FONT: Futura LT Pro Bold

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

PRODUCT FEATURE ICONS




PRODUCT ICON LIBRARY

FEATURE/BENEFIT ICONS

SIZE: Width of the icons should be scaled down to **3/5 the** width of the front panel consumable badge.

SPACING: Relevant product icons (with <u>translations</u> in directly below the icon) should be placed on the left side of the front panel and stacked vertically, **using best judgment** to space them out evenly within the available space.

FONT: Futura LT Pro Bold




Avoid placing translation text over dark red color.

> 2 YEAR

NOTES: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart. If translation text falls over the red background, white text must be used.

Some variations of the clamshell may not allow for artwork to be printed on the left side (i.e. value packs containing consumables.) In this case, icons may be placed on the right side, **using best judgment** in placing the icons. In cases where space is limited, the minimum size for icons should be **2/5 the size** of the consumable badge.



FRONT PANEL FRONT PANEL - ALT LAYOUT

ADDITIONAL PRODUCT CALLOUTS/BADGES



FEATURE & BENEFIT CALLOUTS

Some clamshell packaging layouts may have large dead areas on back panels due to enclosed areas containing cords or accessories. In this situation, utilize the open space found on the bottom of the packaging to place any additional product feature & benefit callouts. For hierarchy purposes, font size should be smaller than that used in the product description (right of the logo.)

FONT: Serifa STD Bold



Example of "Back Flap A" after package assembly.

ADDITIONAL BADGES

Additional badges/icons will live on the back panel within the live content area. Use your spacers to determine the live area, making sure to avoid no print areas (exclude yellow glue gun shape from the live area), then **use best judgment** to place additional badges/icons (with translations placed directly below) using Futura LT Pro Bold.


NOTES: The minimum size for <u>translation</u> text is 4pt, and the translations must always be the same size as its English counterpart.

Additional badges can be downloaded from the icon library.



UPC/SAFETY ICONS/TEXT 8





NOTES: Use best judgment to maintain proper spacing and readability when placing text, UPC, safety icons.

Always confirm the most up to date numbers and information from Product Manager prior to releasing files.

Safety icons can be downloaded from the icon library.

The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.



GLUE STICK BAG OVERVIEW

CLICK ON THE NUMBERS OR TEXT BELOW TO JUMP TO THAT SECTION.





- 1. GRAPHIC ELEMENTS
- 2. ARROW LOGO

- 3. CONSUMABLE BADGE
- 4. PRODUCT WINDOW
- 5. PRODUCT DESCRIPTIONS
- 6. PRODUCT FEATURE ICONS
- 7. ADDITIONAL PRODUCT INFO
- 8. UPC, SAFETY ICONS & TEXT



COMPLETED GLUE STICK BAG TEMPLATE



NOTE: Glue stick bag contains two clear windows that are shown here as "No Print Areas." One is a clear triangle on the front panel and the other spans the entire bottom of the bag.

NOTE: Solid and dotted dielines in the supplied art files denote seams and seals. Use spacing guide as shown in subsequent pages to ensure proper distance between these areas and relevant artwork.

CREATING YOUR SPACING GUIDE

STEP 1 (IMPORTANT)

In this step you will be creating a guide that will determine the spacing for all package design elements. Start by scaling the logo to the full width of the front panel.



STEP 2

Using the logo at this size, **cut the chevron in** half to create your spacing and layout guide. Additionally, in this package type, you will also make use of a **quarter chevron** for smaller spaces. Note color differences below.



SPACER USAGE EXAMPLE

Use half and quarter chevron sizing tool to determine proper spacing of subsequent graphic/text elements as shown below. (Refer to each section for a more detailed guide.)



CLICK HERE

GRAPHIC ELEMENTS (SHORTER BAGS) (1



TO DOWNLOAD THE

PASSWORD: 7Fwcwh4T

METALLIC TEXTURE

To be used as a background image, the metallic texture should be placed in a way that the fade-to-white effect begins above the total template center point.




corner triangle height = 3 quarter chevrons


above center point

CORNER TRIANGLE

To find the height of your corner triangle, add 3 quarter chevrons above the total template center point as pictured to the right. The dark red portion of the triangle should be determined using 3 half chevrons as pictured below.



For the back panel, maintain the size of the large triangle from the front, but fill the entire triangle using the darker red.



total template center point

GRAPHIC ELEMENTS (TALLER BAGS)




GRAPHIC ELEMENTS

PASSWORD: 7Fwcwh4T

METALLIC TEXTURE

To be used as a background image, the metallic texture should be placed in a way that the fade-to-white effect begins above the total template center point.




Corner triangle height

= 3 quarter chevrons below center point

CORNER TRIANGLE


To find the **height** of your corner triangle, **add 3 quarter chevrons below the total template center point** as pictured to the right. The dark red portion of the triangle should be determined using **3 half chevrons** as pictured below.



For the back panel, maintain the size of the large triangle from the front, but fill the entire triangle using the darker red.

FRONT SIDE

BACK SIDE



Total template center point

STEP 1


To determine the size and placement of the logo, place one spacer flush against the secondary top dieline (below punch hole), as well as one flush against the left and right dielines. Then scale the logo to fit within the spacers.

NOTE: Always maintain proper logo ratios as per brand guidelines. Do not stretch or distort the logo to fit.

STEP 2

Once the logo is properly scaled and placed within the top, left, and right spacers, add a half chevron at the bottom to provide extra padding between the logo and lower graphic elements.

BACK PANEL: Logo on the front and back should be the same size, but the logo on the back should be knocked out in all white.



FRONT SIDE



BACK SIDE



CONSUMABLE BADGE (3)


PRODUCT ICON
LIBRARY

STEP 1

For the glue stick bags, the consumable badge is a pre-built element that can be downloaded from the icon library. Check with your project manager for which consumable badge(s) to use.


STEP 2

To determine the correct size of the consumable badge, place 3 consumable badges side by side and horizontally scale to fit the width of the **front** of the package. Place the consumable badge on the right side, 1 spacer down from the bottom of the logo.




FRONT PANEL BADGE width = 1/3 total front panel area

PRODUCT WINDOW (SHORTER BAGS) (4



PRODUCT WINDOW (TALLER BAGS)



FRONT SIDE

PRODUCT DESCRIPTIONS

FRONT SIDE



MAIN PRODUCT DESCRIPTION

To find your live area, place one half chevron spacer flush against the left dieline of your front panel and one flush against the bottom edge (the dieline above the No Print Area). The product description lockup (with <u>translations</u>) will consist of the quantity (considerably larger than the rest of the text), the description, and any relevant translations. Align your text left along the spacer and **use best judgment** for sizing using the image to the left as a guide.

FONT: Futura LT Pro Bold

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

PRODUCT FEATURE ICONS




PRODUCT ICON
LIBRARY

FEATURE/BENEFIT ICONS

SPACING: Relevant product icons (with <u>translations</u> directly below the icon) should be placed on the left side of the front panel, 1 half chevron spacer down from the logo, stacked vertically, **using best judgment** to space them out evenly within the available space.

FRONT SIDE





SIZE: Width of the icons should be scaled down to 2/3 the width of the front panel consumable badge.

FONT: Futura LT Pro Bold

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart. If translation text falls over the red background, white text must be used.

ADDITIONAL PRODUCT CALLOUTS/BADGES



FEATURE & BENEFIT CALLOUTS

To find the live area of your callouts on the back panel, use your half chevron spacer (or quarter chevron if space is very limited) between the logo at the top and the badges/UPC at the bottom. The product description will be in all caps, and the application examples will be about 2 pt sizes smaller. Repeating your initial lockup, add your translations below, stacking vertically. **Use best judgment** in situations where space is extremely limited.

FONT: Serifa STD Bold



BACK SIDE

ADDITIONAL BADGES

Glue stick bags may contain an additional badge that does not exactly fit with the feature/benefit icons (i.e. "ALL PURPOSE"). This badge will be the same width of the other icons, but should be placed (with translations below) in the upper right corner of the front panel, using your half chevron spacer against the edges.

FONT: Futura LT Pro Bold



FRONT SIDE

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

UPC/SAFETY ICONS/TEXT (8)

NOTES: Using your half and quarter chevron spacers as pictured below, find your live area for the UPC/Safety Icons/Text. Place elements according to the hierarchy shown below. The item # and website use the font <u>Futura LT Pro Bold</u>. For all other text in this area, use font <u>Serifa STD Bold</u>. **Use best judgment** to keep font size readable for the consumer, and for the placement of the UPC, safety icons and text. Always maintain spacing from elements and egdes using your half chevron spacer (or quarter chevron spacer when space is extremely limited.)


The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

Safety icons can be downloaded from the icon library.

*Always confirm the most up to date numbers and information from Product Manager prior to releasing files.

BACK SIDE








WRAP-AROUND LABEL LAYOUT OVERVIEW

CLICK ON THE NUMBERS OR TEXT BELOW TO JUMP TO THAT SECTION.



- 1. GRAPHIC ELEMENTS
- 2. CONSUMABLE BADGE
- 3. COLOR BRAND BAR
- 4. ARROW LOGO

- 5. PRODUCT DESCRIPTIONS
- 6. ADDITIONAL PRODUCT INFO
- 7. UPC, SAFETY ICONS & TEXT

STEP 1 (IMPORTANT)

In this step you will be creating a guide that will determine the spacing for all package design elements. Start by scaling the <u>logo</u> to 1/2 the width of the front panel of the package.

RSA3/16IP USE YELLOW RIVET HEAD UTILICE CABEZA DE REMACHE AMARILLA SHORT RIVETS REMACHES CORTOS RIVETS COURTS J/16" Smm GRIP ALUMINUM | ALUMINIO Centerpoint

STEP 2

Using the logo at this size, **cut the chevron in half** to —create your spacing and layout guide. Additionally, in this package type, you will also make use of a quarter chevron for smaller spaces. Note color differences below.



STEP 3

Use half and quarter chevron sizing tool to determine proper spacing of subsequent graphic/text elements as shown below.




GRAPHIC ELEMENTS (1)

TO DOWNLOAD THE **GRAPHIC**

PASSWORD: 7Fwcwh4T

METALLIC TEXTURE

To be used as a background image, the metallic texture should fill approximately 1/2 the height of its respective panel.




Dotted line denotes the centerpoint of the panel.


CORNER TRIANGLE

The corner triangle is a graphic element that should span 1/2 the height of the front panel in its entirety. The dark red portion of the triangle should be determined using 3 half chevrons.

When using the corner triangle on additional panels, simply scale down the existing graphic to 1/2 of your panel size.



FRONT PANEL



CONSUMABLE BADGE



PRODUCT ICON LIBRARY

STEP 1

For wrap-around labels, the consumable badge is a pre-built element that can be downloaded from the icon library. Check with your project manager for which consumable badge(s) to use.

STEP 2

The consumable badge will be located on the right side of the front panel. The width of the consumable badge will be 28% of the width of your **front panel**. The background color of the consumabe badge with span 100% of the height of the front panel.

FRONT PANEL



FRONT PANEL BADGE

width = 28% of the total front


STEP 1

The height of the brand bar should be equal to 1 of your half chevron spacers.



STEP 2

To determine the width of the dark red color, use **7 spacers** flipped 90° to measure the distance from the front panel consumable color badge to the tip of the dark red.



STEP 3

Place one of the flipped spacers from the previous step on the far left side of your brand bar. This will show you where to place your product number (e.g. RSA3/16IP). The height of the product number text should not exceed 50% of the brand bar height and be centered between the top and bottom of the brand bar.

FONT: Futura LT Pro Bold



STEP 1

To determine the size and placement of the logo, place one spacer flush against the far left die line, one against the top brand bar, and one to the left of the consumable badge. Then scale the logo to fit within the spacers.

NOTE: Always maintain proper logo ratios as per brand guidelines. Do not stretch or distort the logo to fit.

STEP 2

Once the logo is properly scaled and placed within the top, left, and right spacers, add an additional half chevron at the bottom to maintain uniform spacing on all sides.

FRONT PANEL





MAIN PRODUCT DESCRIPTION

On the front panel, create a live area for your main product description (and <u>translations</u>) by placing one spacer below the logo, and one on the left edge the panel.

PRODUCT QUANTITY

Place your product quantity (and translations) in the lower portion of the front panel to the left of the consumable badge (if the package contents are greater than 1). Find the live area for the product descriptions by placing 1 spacer against any edges or elements such as the consumable badge or the logo.

PRODUCT MATERIAL

In some cases the wrap-around label may include a description of the product material (and translations). This text can be placed on a black background, and the size determined using your spacers as shown.

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

FONT: Futura LT Pro Bold



ADDITIONAL PRODUCT CALLOUTS



COMPATIBILITY AND GUIDELINES

Utilize the back panel to reference any additional product information (and <u>translations</u>) using the font Serifa STD Bold (paragraph) or Futura LT Pro Bold (headers/callouts). To determine a live area for this section, place a spacer against the top, bottom, and right edge. The use of a spacer against the left die line is preferred but may not be possible in certain situations.

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

FONT: Futura LT Pro Bold / Serifa STD Bold



UPC/SAFETY ICONS/TEXT 7

NOTES: Using your **half chevron** spacer as pictured below, find your live area for the UPC/Safety Icons/Text. Place elements according to the hierarchy shown below, facing in the direction shown in the first graphic to ensure the final assembled package displays all info correctly. The item # and website use the font <u>Futura LT Pro Bold</u>. All other text in this area is use font <u>Serifa STD Bold</u>. **Use best judgment** in font size, and placement of the UPC, safety icons, and text. Always maintain spacing from elements and edges using your half chevron spacer (or quarter chevron spacer when space is extremely limited.)

The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

Safety icons can be downloaded from the icon library.

*Always confirm the most up to date numbers and information from Product Manager prior to releasing files.






CLICK ON THE NUMBERS OR TEXT BELOW TO JUMP TO THAT SECTION.




BACK LABEL



- GRAPHIC ELEMENTS
 COLOR BRAND BAR
- 3. ARROW LOGO
- 4. PRODUCT DESCRIPTIONS
- 5. PRODUCT FEATURE ICONS
- 6. ADDITIONAL PRODUCT INFO
- 7. UPC, SAFETY ICONS & TEXT
- 8. EXTRA CONTENT AREA

COMPLETED LABEL TEMPLATE



NOTE: All graphic elements should be properly spaced from the die line NOT the edge of the label.



CREATING YOUR SPACING GUIDE

STEP 1 (IMPORTANT)

In this step you will be creating a guide that will determine the spacing for all package design elements. Start by scaling the <u>logo</u> to 1/4 the width of the front label of the package.



STEP 2

Using the logo at this size, **cut the chevron in half** to create your spacing and layout guide. Additionally, in this package type, you will also make use of a **quarter chevron** for smaller spaces. Note color differences below.




SPACER USAGE EXAMPLES

Use half and quarter chevron sizing tool to determine proper spacing of subsequent graphic/text elements as shown below.



BACK LABEL




GRAPHIC ELEMENTS (1)



PASSWORD: 7Fwcwh4T


METALLIC TEXTURE

To be used as a background image, the metallic texture should fill approximately 1/2 the height of its respective panel.




CORNER TRIANGLE

The corner triangle is a graphic element that should span 1/2 the height of the front label. The dark red portion of the triangle should be determined using **2 half chevrons**.




FRONT LABEL



STEP 1

The height of the brand bar should be equal to 1 of your half chevron spacers. To determine the width of the dark red color, use 8 spacers flipped 90° (from the far right edge of the panel) to measure the distance from the right edge to the tip of the dark red.



STEP 2

Place one of the flipped spacers from the previous step on the far left side of your brand bar. This will show you where to place your product number (e.g. ROT276-A). The height of the product number text should not exceed 50% of the brand bar height and placed 1 pixel down from the center (to allow for space from the rounded edge).


FONT: Futura LT Pro Bold



STEP 1

To find the size and placement of the logo, divide the front label into thirds. Place 2 spacers flush against the far left die line and 1 against the top brand bar. Then scale the logo until it fits flush to the line for the first third.

NOTE: Always maintain proper logo ratios as per brand guidelines. Do not stretch or distort the logo to fit.



STEP 2

Once the logo is properly scaled and placed, add an additional half chevron at the bottom to maintain uniform spacing on all sides.



BACK PANEL

The size of the logo on the back panel is not the same as the front panel shown above. The width of the logo should equal 1/3 the width of the back panel, then utilize the spacer around all four edges.



PRODUCT DESCRIPTIONS



live area width =

FRONT LABEL

The width of the live area should be 1/3 the width of the front label. Place your main product description (and translations) on the right side of the front label with 2 spacers of padding on the right edge, and 1 from the top and bottom edges. Left-align the text to the edge of the live area.

FONT: Futura LT Pro Bold






BACK LABEL

To find the live area for the product description (and translations) on the back label, place one spacer at the top, one spacer against the logo, and one along the right edge of the label. When done, add a spacer to the bottom to leave distance between live area and other sections.

FONT: Futura LT Pro Bold

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

BACK LABEL



PRODUCT FEATURE ICONS





FEATURE/BENEFIT ICONS

Product feature icons (with <u>translations</u> stacked directly below) should be located in the area between the logo and the product descriptions. All feature/benefit icons can be accessed and downloaded via the icon library link in the upper left.

SIZE: The size of the icons should ideally be equal to the height of the logo but in situations where there are more icons they may be scaled down smaller to fit the live area. **Use best judgment.**

SPACING: Icons and translations should be placed side-by-side (horizontally) and spaced evenly from one another within the live area.

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.



ADDITIONAL PRODUCT CALLOUTS/BADGES



FEATURE & BENEFIT CALLOUTS

To find the live area of your callouts on the back label, use your half chevron spacer (or quarter chevron if space is very limited) below the logo/product description area at the top and above the badges/UPC at the bottom. Also use a half chevron spacer on the left and right edges of the back label. **Use best judgment** to maintain readability in situations where space is extremely limited.

FONT: Serifa STD Bold

BACK LABEL



NOTE: <u>Translations</u> are not possible for every single item described in the kit, but the main categories (i.e. cutting, sanding, grinding) should include a translation. The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

UPC/SAFETY ICONS/TEXT 7

NOTES: Using your half and quarter chevron spacers as pictured below, find your live area for the UPC/Safety Icons/Text. Place elements according to the hierarchy shown below. The item # and website use the font <u>Futura LT Pro Bold</u>. For all other text in this area, use font <u>Serifa STD Bold</u>. **Use best judgment** to keep font size readable for the consumer, and for the placement of the UPC, safety icons and text. Always maintain spacing from elements and egdes using your half chevron spacer (or quarter chevron spacer when space is extremely limited.)


The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

Safety icons can be downloaded from the icon library.

*Always confirm the most up to date numbers and information from Product Manager prior to releasing files.



BACK LABEL



Depending on the product type, this area should be used for any legal mandatories such as product warnings (and <u>translations</u>). **Use your best judgment** on spacing based on the required text for each product. Make sure to maintain proper padding around text area by utilizing your spacer.


NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.



SLEEVE LAYOUT OVERVIEW

CLICK ON THE NUMBERS OR TEXT BELOW TO JUMP TO THAT SECTION.





BOTTOM PANEL



- 1. GRAPHIC ELEMENTS
- 2. COLOR BRAND BAR
- 3. ARROW LOGO

- 4. PRODUCT DESCRIPTIONS
- 5. PRODUCT FEATURE ICONS
- 6. PRODUCT PHOTOGRAPHY
- 7. ADDITIONAL PRODUCT INFO
- 8. UPC, SAFETY ICONS & TEXT
- 9. EXTRA CONTENT AREA

COMPLETED SLEEVE TEMPLATE



CREATING YOUR SPACING GUIDE

STEP 1 (IMPORTANT)

In this step you will be creating a guide that will determine the spacing for all package design elements. Start by scaling the <u>logo</u> to 1/2 the width of the front panel of the package.



STEP 2

Using the logo at this size, **cut the chevron in half** to create your spacing and layout guide. Additionally, in this package type, you will also make use of a **quarter chevron** for smaller spaces. Note color differences below.



SPACER USAGE EXAMPLE

Use half and quarter chevron sizing tool to determine proper spacing of subsequent graphic/text elements as shown below.



GRAPHIC ELEMENTS (1)



PASSWORD: 7Fwcwh4T

METALLIC TEXTURE

To be used as a background image, the metallic texture should fill approximately 1/2 the height of its respective panel.



CORNER TRIANGLE

The corner triangle is a graphic element that should span 1/2 the height of the front panel. The dark red portion of the triangle should be determined using **3 half chevrons**. For the bottom panel, use the corner triangle you created on the front panel and proportionally scale the triangle to about 1/2 the height of the bottom panel. **Use best judgment**.



FRONT PANEL



BOTTOM PANEL



COLOR BRAND BAR (2)

STEP 1

The height of the brand bar should be equal to 1 of your half chevron spacers.



FRONT PANEL

STEP 2

To determine the width of the dark red color, use 7 spacers flipped 90° to measure the distance from the right edge to the tip of the dark red.



STEP 3

Place one of the flipped spacers from the previous step on the far left side of your brand bar. This will show you where to place your product number (e.g. ROT276-A). The height of the product number text should not exceed 50% of the brand bar height and placed 1 pixel down from the center of the brand bar. (See product description section for placement of product numbers when no brand bar is present).

FONT: Futura LT Pro Bold



NOTE: "ROT4500K-A" (the item #) may also appear in other areas outside of the color brand bar. **See** "Product description" section.

STEP 1

To determine the size and placement of the logo, place one spacer flush against the far left die line, one against the top brand bar, and one flush against the centerpoint. Then scale the logo to fit within the spacers.

NOTE: Always maintain proper logo ratios as per brand guidelines. Do not stretch or distort the logo to fit.



STEP 2

Once the logo is properly scaled and placed within the top, left, and right spacers, add an additional half chevron at the bottom to maintain uniform spacing on all sides.



PRODUCT DESCRIPTIONS

FRONT PANEL

To find the size of your product description (and <u>translations</u>) live area, place one spacer from the right die line, one from the top brand bar, and one to the right of the logo. Make sure to keep one spacer's distance from all imagery and icons below.



FONT: Futura LT Pro Bold

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

BACK PANEL

To determine your live area on the back panel, place two spacers down from the top die line, one spacer from the right die line, and one to the right of the logo. Then place one spacer below the live area box to maintain spacing from other elements.

ITEM # PLACEMENT: The item # should be placed 1 quarter chevron spacer from the top, 1 half chevron spacer from the right edge of the panel.



BOTTOM PANEL

Similar to the front panel, your live area will keep one spacer from the logo, one from the top, and one from the right die line. Due to a lack of space, maintain at least one quarter chevron spacer from the icons below.



PRODUCT FEATURE ICONS



PRODUCT ICON LIBRARY

FRONT PANEL

Product feature icons (and <u>translations</u> stacked vertically below) should be located below the product descriptions, on the right side of the front panel. First, add 1 half chevron spacer below the product description, 1 spacer flush against the bottom edge, and 1 spacer against the right edge. The live area can then extend to the centerpoint of the front panel. **Use best judgment** to position icons within the available space.

SIZE: Icons should not exceed a width of 3 half chevron spacers (flipped 90 degrees) and should not be smaller than 2 half chevron spacers (flipped 90 degrees).



SPACING: Icons can be placed horizontally, vertically, or a combination of both (**use best judgment** based on available space.) Regardless, spacing between the icons and tranlations should remain consistent.



BOTTOM PANEL

Product feature icons (and translations stacked vertically below) should be located below the product descriptions. First, add 1 quarter chevron spacer below the product description, 1 quarter chevron spacer flush against the bottom edge, and 1 half chevron spacer against the right edge. Be sure to reserve some space for the product photography below the logo. **Use best judgment** to position icons within the available space.



SIZE: Due to the extremely limited space on the bottom panel, the width of the icons will a approximately 2 half chevron spacers (flipped 90 degrees).



SPACING: Icons on the bottom panel will be placed horizontally within the live area. Spacing between the icons and transations should remain consistent.

NOTE: The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

FRONT PANEL

Product photography for sleeves should include the tool, all accessories, and carrying case. Determine a live area for your product photography by adding a spacer around all of the elements you've placed on the panel.



BACK PANEL

The right side of the panel will be reserved for additional content. Therefore, to determine the photography live area on the back panel, place one spacer from the left die line and one from the center point. You will also maintain one spacer distance from content areas above and below.



BOTTOM PANEL

Space is very limited on the bottom panel, so determine the live area for this panel by placing a quarter chevron spacer along the left edge, one below the logo, and one along the bottom edge. Try to maintain at least one half chevron spacer between the photography live area and the product icons.



ADDITIONAL PRODUCT CALLOUTS/BADGES




FEATURE & BENEFIT CALLOUTS

To find the live area of your callouts on the back label, use your half chevron spacer against all panel edges and around and other graphic/text elements. **Use best judgment** in situations where space is extremely limited.

FONT: Serifa STD Bold

NOTE: <u>Translations</u> are not possible for every single item described in the kit, but the main categories (i.e. cutting, sanding, polishing) should include a translation. The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

BACK PANEL



NOTES: Using your half chevron spacers as pictured below, find your live area for the UPC/Safety Icons/Text. Place elements according to the hierarchy shown below. The item # and website use the font <u>Futura LT Pro Bold</u>. All other text in this area is use font <u>Serifa STD Bold</u>.

Use best judgment to keep font size readable for the consumer, and for the placement of the UPC, safety icons, and text. Always maintain spacing from elements and egdes using your half chevron spacer (or quarter chevron spacer when space is extremely limited.)

The minimum size for <u>translation</u> text is 4pt, and the translations must always be the same size as its English counterpart.

Safety icons can be downloaded from the icon library.

*Always confirm the most up to date numbers and information from Product Manager prior to releasing files.

COPYRIGHT INFO

CORPORATE

ADDRESS

MANUFACTURING

LOCATION

(and translations)

BACK PANEL



BACK PANEL



NOTES: Depending on the product type, this area located on the back panel should be used for any legal mandatories such as product warnings. **Use your best judgment** on spacing based on the required text for each product. Make sure to maintain proper padding around text area by utilizing your spacer.

Safety icons can be downloaded from the icon library.


The minimum size for translation text is 4pt, and the translations must always be the same size as its English counterpart.

*Always confirm the most up to date numbers and information from Product Manager prior to releasing files.





MASTER / INNER CARTON LAYOUT OVERVIEW

CLICK ON THE NUMBERS OR TEXT BELOW TO JUMP TO THAT SECTION.




COMPLETED MASTER / INNER CARTON TEMPLATES





STEP 1 (IMPORTANT)

In this step you will be creating a guide that will determine the spacing for all package design elements. Whether you are working with a wide or tall box template, start by scaling the logo to 1/2 the width of the primary side panel of the package.



STEP 2

Using the logo at this size, **cut the chevron in half** to create your spacing and layout guide.



SPACER USAGE EXAMPLE

Use half chevron sizing tool to determine proper spacing of subsequent graphic/text elements as shown below.

PRIMARY SIDE PANEL




WIDE BOX

PRIMARY SIDE PANEL: To determine the size and placement of the logo on the primary side panel, place 1 spacer flush against the top die line, 1 against the left die line, and 1 against the left side of the centerpoint. Then, scale the logo to fit within the spacers.




TOP PANEL: Place the logo on the top panel 1 spacer from the left edge, 1 spacer from the bottom edge, and 1 against the left side of the centerpoint. Then, scale the logo to fit within the spacers.



NOTE: Always maintain proper logo ratios as per brand guidelines. Do not stretch or distort the logo to fit.

TALL BOX

PRIMARY SIDE PANEL: To determine the size and placement of the logo on the primary side panel, place two spacers flush against the top die line and one against the left die line. Then scale the logo until it fits within the spacers and is flush to the centerpoint.



TOP PANEL: Using the same size logo from the previous step, place the logo on the top panel 1 spacer from the left edge and 1 spacer from the bottom edge. It should rest flush against the centerpoint.



MAIN PRODUCT DESCRIPTION

Whether you are working with a wide or tall box template, determine the live area of your product description on the primary side panel by placing 1 spacer against the right edge of the logo and 1 spacer on the right edge of the panel. Left align the text, and align text to the top of the logo (two spacers from the top edge). Font size is dependent on the available space, **use best judgment** using the photos below as a guide.

FONT: Futura LT Pro Bold

TALL BOX - PRIMARY SIDE PANEL



WIDE BOX - PRIMARY SIDE PANEL





NOTE: Located on the primary side panel, the UPC area for the master / inner carton is comprised of the UPC, the item number, carton quantity, and manufacturing location.


WIDE BOX

To determine the live area for the UPC lockup, place 1 spacer flush against the bottom edge, the right edge, and below the bottom of the product description. The live area can extend all the way to the panel centerpoint. Align the UPC lockup to the left and bottom of the live area as shown.



TALL BOX

To determine the live area for the UPC lockup, place 4 spacers flush against the bottom edge, 4 below the bottom of the product description, 1 against the right edge, and 1 against the right side of the logo. Then, scale the UPC lockup to fit the width of the live area and align to the bottom of the live area.



PRODUCT ILLUSTRATION



PRODUCT ICON
LIBRARY

WIDE BOX

The product illustration is located on the primary side panel, below the logo and to the left of the UPC lockup. To find the live area, add 1 spacer below the logo, 1 spacer against the bottom edge of the panel, 2 spacers against the left edge of the panel, and 2 spacers against the left edge of the UPC lockup. Align the illustration to the bottom edge of the live area, and center it horizontally.


PRIMARY SIDE PANEL



TALL BOX

The product illustration is located on the primary side panel, below the logo and to the left of the UPC lockup. To find the live area, add 4 spacers below the logo, 4 spacers against the bottom edge of the panel, 2 spacers against the left edge of the panel, and 2 spacers against the left edge of the UPC lockup. Align the illustration to the bottom edge of the live area, and center it horizontally.

PRIMARY SIDE PANEL



NOTE: Located on the secondary side panels, the graphic elements for the master / inner cartons are comprised of the icon from the arrow logo, and a footer at the bottom of the panel that contains either the corporate address (secondary side panel A) or the Arrow website (secondary side panel B).


WIDE BOX

STEP 1: Starting with secondary side panel A, create a footer that spans the width of the panel. The height of the black strip will be 2 spacers from the bottom edge.

STEP 2: Next, insert the Arrow corporate address as shown using Futura LT Pro Bold (knocked out), centering the text vertically and horizontally within the black strip.

STEP 3: Find the live area of the Arrow icon by placing 1 spacer flush against the top of the black strip, and 1 flush against the top edge of the panel. Center the Arrow icon vertically and horizontally within the live area.

STEP 4: For secondary side panel B, duplicate artwork for the previous steps and replace the corporate address with the Arrow website.




TALL BOX

STEP 1: Starting with secondary side panel A, create a footer that spans the width of the panel. The height of the black strip will be 2 spacers from the bottom edge.

STEP 2: Next, insert the Arrow corporate address as shown using Futura LT Pro Bold (knocked out), centering the text vertically and horizontally within the black strip.

STEP 3: Determine the size of the Arrow icon by scaling it to 50% of the height of the remaining white space. Center the Arrow icon vertically and horizontally within the white space.


STEP 4: For secondary side panel B, duplicate artwork for the previous steps and replace the corporate address with the Arrow website.



BOTTOM PANEL PRODUCT INFO

Whether you are working with a short or tall box template, determine the live area of your product description by placing one spacer against all four edges of the panel. Keeping text on a single line, use <u>Futura LT Pro Bold</u> and center the text horizontally and vertically. Font size is dependent on the available space, **use best judgment** using the photos below as a guide.

NOTE: Located on the bottom panel, the additional product info for the master / inner carton is comprised of the copyright info, revision date, and packaging material number.









WHAT IS A TOOL LABEL?

Tool labels are stickers or graphics placed directly on the tool showcasing a logo and/or important safety or model information.

NOTES: To determine whether the product you are designing for requires a tool label, **check with your project manager.** Information shown on tool labels will vary, and your project manager can confirm this information.

Tool labels will have a solid black backround, all text will be white, and show the version of the Arrow logo with white/red and no tagline as shown below.

Due to the extremely limited space available when designing a tool label, **use best judgment** in sizing the logo and text, making it as large as possible while maintaining sufficient clearance from the die line.

Safety icons can be downloaded from the icon library.

*Always confirm the most up to date numbers and information from Product Manager prior to releasing files.

TOOL LABEL LAYOUT EXAMPLES





BRAND TEAM CONTACT

Arrow Fastener Co., LLC 271 Mayhill Street Saddle Brook, NJ 07663 800.776.2228 brandteam@arrowfastener.com